

Auto...
Helikopter...

SERVO's



Einsatz- zweck:	Auto				Helikopter					
	Speed		Torque		Speed		Torque		Heckrotor	
Artikelnummer:	DS700	DS1000	DT750	DT1100	HS700	HS1000	HT750	HT1100	HG800	HG900
Betriebsspannung:	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	6.0 V - 7.4 V	4.8 V - 6.0 V	4.8 V - 6.0 V
Stellkraft (7.4V):	11.10 kgcm	11.50 kgcm	16.20 kgcm	16.80 kgcm	11.10 kgcm	16.10 kgcm	16.80 kgcm	18.40 kgcm	6.40 kgcm	6.40 kgcm
Stellkraft (6.0V):	9.60 kgcm	10.20 kgcm	13.80 kgcm	14.20 kgcm	9.90 kgcm	13.20 kgcm	14.20 kgcm	15.60 kgcm	5.20 kgcm	5.20 kgcm
Geschwindigkeit (7.4V):	0.06 s/60°	0.06 s/60°	0.09 s/60°	0.09 s/60°	0.06 s/60°	0.06 s/60°	0.09 s/60°	0.09 s/60°	0.04 s/60°	0.04 s/60°
Geschwindigkeit (6.0V):	0.08 s/60°	0.08 s/60°	0.12 s/60°	0.12 s/60°	0.08 s/60°	0.08 s/60°	0.12 s/60°	0.12 s/60°	0.05 s/60°	0.05 s/60°
Elektronik:	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital
Gehäuse:	Alu - Mittelteil	Alu	Alu - Mittelteil	Alu	Alu - Mittelteil	Alu	Alu - Mittelteil	Alu	Alu - Mittelteil	Alu
Kugellager:	2	2	2	2	2	2	2	2	2	2
Getriebe:	Metall	Metall	Metall	Metall	Metall	Metall	Metall	Metall	Metall	Metall
Motor:	Coreless	Coreless	Coreless	Coreless	Coreless	Coreless	Coreless	Coreless	Coreless	Coreless
Gewicht:	57.8 g	68.5 g	59.1 g	70.4 g	62.1 g	72.3 g	62.4 g	72.6 g	62.0 g	71.8 g
Abmessungen:	39.5x20.0x38.3 mm	39.5x20.0x38.7 mm	39.5x20.0x38.3 mm	39.5x20.0x38.7 mm	39.5x20.0x38.6 mm	39.5x20.0x38.7 mm	39.5x20.0x38.6 mm	39.5x20.0x38.7 mm	39.5x20.0x38.7 mm	39.5x20.0x38.7 mm
Verzahnung:	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne	25 Zähne